

Conventional Manual Call Point

MODEL: **BG-MS-2**

BG-MS-2 is a call point designed to provide a manual alarm interface to any conventional fire alarm control panel. MCPs are made of CRCA sheet as per the IS standards. There is a transparent glass protecting the MCP from the front side. A small MS powder coated hammer is attached with the MCP, This is used to break the front glass to generate alarm in the system. All the MCP comes with a factory fitted back box for Surface or Semiflsh mounting on the wall.

Features:

- **Compatibility with any conventional fire Alarm System**
- **Wall mount facility**
- **Suitable for malls, restaurant, residential etc.**
- **Duel LED on front**
- **Steady RED LED at fire condition**
- **Green LED blinking at normal condition (optional)**



Specification:

Operating voltage	24V DC
Current Consumption (Normal/fire)	150µA/ 60mA@ 24 VDC
Application Temp range	0° C to + 60° C
Humidity	5 to 95% Relative Humidity (non condensing)
Housing	CRCA Sheet (1.6 mm thick)
Weight	475gm
Dimensions (mm)	120 x 95 x 58 (W x H x D)
Colour	Red

Operation:

To operate the MCP, break the front glass with attached hammer. Steady glow of Red LED will indicate the activation of MCP. TO reset the MCP open the front cover & change the glass.

Ordering Information:

Part Number	Pack Quantity	Dimensions (WxHxD millimetres)	Weight
BG-MS-2	4 Units	200 x 125 x 125	750g